



Nominal Pipe Size NPS	O.D. of Flange O	Thickness ⁽¹⁾		Length Through Hub ⁽¹⁾ Y	Hub Dia. at Base X	Hub Dia. at End A	Diameter of Raised Face R	Drilling			Diameter of Bolts	Radius of Fillet r	Approximate Weight each/lbs.	
		W/N t _f (min)	Blind t _f (min)					Diameter of Bolt Circle W	Number of Bolt Holes	Diameter of Bolt Holes			W/N	Blind
		26	34.12					3.44	3.44	5.63			27.62	26.19
28	36.25	3.44	3.44	5.81	29.75	28.19	31.00	33.75	36	1 3/8	1 1/4	0.56	445	964
30	39.00	3.63	3.63	6.16	32.00	30.25	33.25	36.25	36	1 1/2	1 3/8	0.56	548	1175
32	41.50	4.00	4.00	6.56	34.00	32.25	35.50	38.50	32	1 5/8	1 1/2	0.62	672	1472
34	43.62	4.00	4.00	6.75	36.12	34.25	37.50	40.62	36	1 5/8	1 1/2	0.62	723	1624
36	46.12	4.00	4.00	7.06	38.00	36.25	39.75	42.88	32	1 3/4	1 5/8	0.62	808	1822
38	48.12	4.31	4.31	7.50	40.00	38.25	41.75	44.88	36	1 3/4	1 5/8	0.62	904	2136
40	50.12	4.50	4.50	7.75	42.00	40.25	43.88	46.88	40	1 3/4	1 5/8	0.62	977	2410
42	52.50	4.63	4.63	8.00	44.00	42.31	46.00	49.00	36	1 7/8	1 3/4	0.62	1093	2727
44	54.50	4.94	4.94	8.38	46.19	44.31	48.00	51.00	40	1 7/8	1 3/4	0.62	1210	3129
46	57.50	5.00	5.06	8.69	48.38	46.31	50.00	53.75	36	2	1 7/8	0.62	1426	3583
48	59.50	5.00	5.25	8.75	50.31	48.31	52.25	55.75	40	2	1 7/8	0.62	1469	3979
50	61.50	5.38	5.44	9.19	52.38	50.31	54.25	57.75	44	2	1 7/8	0.62	1621	4389
52	63.50	5.56	5.61	9.50	54.44	52.31	56.25	59.75	48	2	1 7/8	0.62	1729	4826
54	65.88	5.32	5.81	9.38	56.50	54.31	58.25	62.12	48	2	1 7/8	0.62	1804	5427
56	69.50	6.00	6.12	10.50	58.81	56.31	60.50	65.00	36	2 3/8	2 1/4	0.69	2412	6330
58	71.94	6.00	6.31	10.75	60.94	58.31	62.75	67.44	40	2 3/8	2 1/4	0.69	2584	7000
60	73.94	5.88	6.50	10.63	62.94	60.31	65.00	69.44	40	2 3/8	2 1/4	0.69	2629	7635

All dimensions are given in inches

Notes:

(1) 1/16" RF NOT included in Flange Thickness (t_f) and Length Through Hub (Y).